

# Fiber Connector Cleaner

## FFC-100 and FFC-200

Dirt, dust and other contaminations are the enemy of high-speed communications over optical fiber link. Maximally using fiber resource requires that all optical connections are clean and free of contaminants.

FibreOptica's FFC-100, the reel-type optic fiber end-face cleaner with one open-window designed in a way of handy operation for all kinds of connectors (SC, SC2, FC, ST, E2000, DIN, D4, MU, LC, MT and etc) and FFC-200 with a two-slots window suitable for all kinds of 1.25mm and 2.5mm connectors, can fast and completely remove dust, dirt and other contaminations.

### Features

- **Safe and environment friendly** - No chemicals and other waste such as alcohol, methanol, cotton tips or lens tissue; safe to operate and no hazard to environment; no ESD contamination.
- **User-friendly** - With few simple steps, ideal cleaning result can be achieved no matter the connector is contaminated by oil or dust.
- **Excellent results** - Fast, effective, repeatable cleanings
- **Economical** - New design for low cost; One reel tape is good for over 500 times cleaning and the cartridge can be easily replaced.
- **Wide application areas** - It is suitable for using in lab environment, fiber cable construction and maintenance, fiber optic components assembly line and etc.



### Specification

Models	FFC-100 One Open-Window	FFC-200 Two-Slots Window
Applying connector	SC, SC2, FC, ST, E2000, DIN, D4, MU, LC, MT	SC, SC2, FC, ST, E2000, DIN, D4, MU, LC
Cleaning Times	Over 500 times per reel	
Cleaning Result	-20 to -50 dB (Return Loss)	
Operating Temperature	-10°C ~ +50°C	
Weight	100 g	

### Ordering Information

FFC-□-0-□

Replacement Reel Tape:  
1 – For One Open-Window  
2 – For Two-Slots Window

Cleaner Type:  
1 – One Open-Window including one FFC-101  
2 – Two-Slots window including one FFC-202